





MANUFACTURED BY OSMA.
45 YEARS OF QUALITY..GUARANTEED!



Technical

		MF100LX-C/Q	MF130LX-C/Q	MF100M-C/Q	MF130M-C/Q	MF160M-C/Q
Excavator Weight Range	tonnes	8-12	9-12	12-16	14-20	14-20
Mulcher Weight w/o Bracket	kg	765	830	860	940	1050
Oil flow requirement	l/min	80-100	90-100	110-130	120-140	120-140
Max Hyd Circuit pressure	bar	220-250	220-250	220-250	220-250	220-250
Cut width	mm	1000	1300	1050	1300	1600
Max cut diameter	mm	200	200	250	250	250
Rotor type		Fixed tool rotor				
Standard motor size	СС	47	47	56	56	56
Total Width	mm	1250	1500	1250	1500	1800



MF130M-C/Q

MF130LX-C/Q







AT A GLANCE

- 'Depth Control Rotor (DCR) for maximum efficiency'
- To suit excavators from 8-20 tonnes(std configuration). Also available for compact loader & skid steer applications.
- Cut capability for grass and vegetation up to 250 mm diameter.
- Heavy duty casing manufactured from Weldox 700 steel for maximum strength and durability.
- Internal frame and counter blades manufactured from Hardox 400.
- Piston motor gives optimum power output.
- Variable displacement motor option.
- · Multi-belt transmission.
- Hydraulic operation of front cover.
- Manufactured by Osma..45 years of quality guaranteed!



US Partner / Distributor



Address: 106 Ark Road Lumberton, NJ 08048

Phone: 888-280-1710 Email: sales@ransomeattach.com

MIDI FOREST

No Compromise



- Vegetation Control.
- Site Clearance.
- Thinning Operations.
- Embankment Maintenance.
- Whole Trees, Scrub, Grass.
- Boundary Restoration.
- Woodland Maintenance.



Exac-One Ltd The Mount Buildings **Tunnel Hill** Upton on Severn Worcestershire WR8 0QL UK

+44 (0)1684 593052

www.exac-one.co.uk info@exac-one.co.uk