



MIDI-MOWER

Vegetation Control

Site Clearance

Thinning Operations

Embankment Maintenance

Hedges, Scrub, Grass

Boundary Restoration

Woodland Maintenance

Range of mowers to suit excavators from 6-18 tonnes and also tractors, loaders and skid steers

Cut capability for grass and vegetation up to 100mm diameter

Casing manufactured using Domex 700 steel for exceptional strength and durability

Piston motors & belt drive (x3 & x4) for maximum power and efficiency

Adjustable rear roller

Choice of flail options

Options – floating link, flow control valve, drainless piston motors

“Perfect Partners”



Exac-One Ltd
The Mount Buildings
Upton on Severn
Worcs
WR8 0QL
United Kingdom

Tel: +44(0)1684 593052
Fax: +44(0)1684 592249
info@exac-one.co.uk
www.exac-one.co.uk

Midi Mower Technical

		TPC100EL	TPC130EL	TPC160EP	TPC190EP
Excavator Weight Range	tonnes	6-8	8-10	10-15	12-18
Mulcher Weight w/o Bracket	kg	380	460	590	680
Oil flow requirement	l/min	60-90	60-90	100-140	100-140
Max Hyd Circuit pressure	bar	240	240	250	250
Cut width	mm	1050	1300	1600	1900
Max cut diameter	mm	75	75	100	100
Total Width	mm	1250	1500	1850	2150