



MINI FOREST



MINI FOREST RANGE
NO COMPROMISE



MANUFACTURED BY OSMA.

40 YEARS OF QUALITY..GUARANTEED!



Technical

Model	Excavator Weight Range (Tonnes)	Mulcher Weight w/o Bracket (kg)	Oil Flow Requirement (L/min)	Max Hyd Circuit Pressure (bar)	Cut Width (mm)	Max Cut Diameter (mm)	Standard Rotor Type	Standard Motor Size (cc)	Total Width (mm)
Drum Rotor									
TF80-XL	5-6.5	375	60-70	220-250	800	150	Drum rotor with heavy hammers	25	1000
TF100-XL	5-7.5	414	60-70	220-250	1000	150	Drum rotor with heavy hammers	34	1200
TF100-L	7-12	650	90-100	220-250	1050	150	Drum rotor with heavy hammers	47	1250
TF130-L	9-12	790	90-100	220-250	1300	150	Drum rotor with heavy hammers	47	1500
Fixed Tool Rotor									
TFK70	2.5-5	285	30	220-250	700	150	Fixed tool Rotor	12	880
TFK90	4-6	335	45	220-250	900	150	Fixed tool Rotor	17	1080
TF80XL-Q	5-6.5	525	50-75	220-250	800	150	Fixed tool Q Rotor	25	1000
TF100XL-Q	6-9	575	60-80	220-250	1000	150	Fixed tool Q Rotor	34	1200
TF100L-Q	8-12	765	80-100	220-250	1000	200	Fixed tool Q Rotor	47	1250
TF130L-Q	9-12	830	90-100	220-250	1300	200	Fixed tool Q Rotor	47	1500



TF100 XL

TF130 L



TFK 70

AT A GLANCE

- Available with Drum Rotor or Fixed Tool Rotor.
- To suit excavators from 2.5 tonnes to 12 tonnes (std configuration) also available for tractors, loaders and skid steers.
- Cut capability for grass and vegetation up to 200mm diameter.
- Heavy duty casing manufactured from Weldox 700 steel for maximum strength and durability.
- Internal frame and counter blades manufactured from Hardox 400.
- Piston motor gives optimum power output.
- Multi-belt transmission.
- Hydraulic operation of front cover.
- Manufactured by Osma..40 years of quality guaranteed!



TF100 XLQ

MINI FOREST

No Compromise

MINI FOREST

- Vegetation Control.
- Site Clearance.
- Thinning Operations.
- Embankment Maintenance.
- Whole Trees, Scrub, Grass.
- Boundary Restoration.
- Woodland Maintenance.



Exac-One Ltd
The Mount Buildings
Tunnel Hill
Upton on Severn
Worcestershire
WR8 0QL
UK

+44 (0)1684 593052

www.exac-one.co.uk
info@exac-one.co.uk