



**MINI MOWER**



**MINI MOWER RANGE**  
NO COMPROMISE





**Manufactured by Osma.**  
**40 years of quality...guaranteed!**



## Technical

Model	Excavator Weight Range (Tonnes)	Mower Weight w/o Bracket (kg)	Oil Flow Requirement (L/min)	Max Hyd Circuit Pressure (bar)	Cut Width (mm)	Max Cut Diameter (mm)	Standard Rotor Type	Standard Motor Size (cc)	Total Width (mm)
TE60 DXL	1-2	70	20-30	160	600	10	TYPE H	8	800
TE80 DXL	1.5-2.5	85	20-30	160	800	10	TYPE H	8	1000
TE80 DL	2-3.5	100	30-45	170	800	50	TYPE RM7	11	1000
TE100 DL	2.5-4	120	30-50	170	1000	50	TYPE RM7	16	1150
TE80 DP	2.5-5	170	30-50	180	800	50	TYPE RM7	11	1100
TE100 DP	2.5-5	195	40-60	180	1000	50	TYPE RM7	16	1300
TE120 DP	4-8	230	50-70	180	1200	50	TYPE C	22	1500
TE100 CL	6-10	315	60-70	190-200	1050	70	TYPE C	34	1250
TE120 CL	6-10	345	60-70	190-200	1250	70	TYPE C	34	1400

**TE80 DXL**



**TE80 DP**

## AT A GLANCE

- To suit excavators from 1 – 10 tonne (std configuration) also available for loaders and skid steers.
- Cut capability for grass and vegetation up to 70mm diameter.
- Manufactured using high grade structural and wear resistant steels, for exceptional strength and durability.
- Adjustable rear roller.
- Choice of flails (does not apply to DXL models).
- Options – floating link, flow control valve, jack stand.
- Manufactured by Osma...40 years of quality guaranteed!



### TE120 DP





---

# MINI MOWER

No Compromise

---

## MINI MOWER

- Vegetation Control.
- Site Clearance.
- Thinning Operations.
- Embankment Maintenance.
- Hedges, Scrub, Grass.
- Boundary Restoration.
- Woodland Maintenance.



---

Exac-One Ltd  
The Mount Buildings  
Tunnel Hill  
Upton on Severn  
Worcestershire  
WR8 0QL  
UK

+44 (0)1684 593052

[www.exac-one.co.uk](http://www.exac-one.co.uk)  
[info@exac-one.co.uk](mailto:info@exac-one.co.uk)